



Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

UVN™ 30-0.8L NEGATIVE DUV PHOTORESIST

Revision date: 06/06/2005

Supplier

ROHM AND HAAS ELECTRONIC MATERIALS LLC
A Subsidiary of The Dow Chemical Company
455 FOREST STREET
MARLBOROUGH, MA 01752 United States

For non-emergency information contact: 215-592-3000

For non-emergency information contact: 508-481-7950

Emergency telephone number

1 800 424 9300

Local emergency telephone number

989-636-4400

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Electronic grade propylene glycol monomethyl ether acetate	108-65-6	60.0 - 95.0 %
Phenolic Resin		< 20.0 %
Ethyl lactate	97-64-3	< 15.0 %
Photoactive compound		< 2.0 %
Polymeric dye		< 5.0 %
Amidomethyl ether crosslinker		< 3.0 %

3. HAZARDS IDENTIFICATION

Emergency Overview

Appearance

Form liquid

Colour clear

Odour Sweet odor

Hazard Summary**WARNING!**

Combustible liquid and vapor. Causes irritation to eyes, nose, and respiratory tract.
Prolonged, repeated contact, inhalation, ingestion, or absorption through the skin, may cause toxic effects to internal organ systems.
May cause allergic respiratory reaction and/or skin reaction.

Potential Health Effects

Primary Routes of Entry: Inhalation, ingestion, eye and skin contact, absorption.

Eyes: May cause pain, transient irritation and superficial corneal effects.

Skin: Material may cause irritation.

Prolonged or repeated exposure may have the following effects:

allergic sensitization
defatting of skin leading to irritation and dermatitis
central nervous system depression
liver damage
kidney damage

Ingestion: Swallowing may have the following effects:

irritation of mouth, throat and digestive tract

headache

nausea

vomiting

Repeated doses may have the following effects:

central nervous system depression

liver damage

kidney damage

Inhalation: Inhalation may have the following effects:

irritation of nose, throat and respiratory tract

Higher concentrations may have the following effects:

systemic effects similar to those resulting from ingestion

Target Organs: Eye

Respiratory System

Skin

nervous system

Liver

kidney

Carcinogenicity

Not considered carcinogenic by NTP, IARC, and OSHA

4. FIRST AID MEASURES

Inhalation: Remove from exposure. If there is difficulty in breathing, give oxygen. Seek medical attention if symptoms persist.

Skin contact: Wash skin with water. Continue washing for at least 15 minutes. Obtain medical attention if blistering occurs or redness persists.

Eye contact: Immediately flush the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.

Ingestion: Wash out mouth with water. Have victim drink 1-3 glasses of water to dilute stomach contents. Induce vomiting if person is conscious. Immediate medical attention is required. Never administer anything by mouth if a victim is losing consciousness, is unconscious or is convulsing.

Notes to physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flash point 43 °C (109.9 °F)
Lower explosion limit No data available
Upper explosion limit No data available

Suitable extinguishing media: Use water spray, foam, dry chemical or carbon dioxide.
 Keep containers and surroundings cool with water spray.

Specific hazards during fire fighting: This product may give rise to hazardous vapors in a fire. Vapors can travel a considerable distance to a source of ignition and result in flashback.

Special protective equipment for fire-fighters: Wear full protective clothing and self-contained breathing apparatus.

Further information: Pressure may build up in closed containers with possible liberation of combustible vapors.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Wear suitable protective clothing.
 Wear respiratory protection.
 Eliminate all ignition sources.

Environmental precautions

Prevent the material from entering drains or water courses.
 Do not discharge directly to a water source.
 Advise Authorities if spillage has entered watercourse or sewer or has contaminated soil or vegetation.

Methods for cleaning up

Contain spills immediately with inert materials (e.g., sand, earth).
 Transfer into suitable containers for recovery or disposal.
 Finally flush area with plenty of water.

7. HANDLING AND STORAGE

Handling

Use local exhaust ventilation. Avoid contact with eyes, skin and clothing. Keep container tightly closed.

Further information on storage conditions: Keep away from heat, sparks, flame, and other sources of ignition. Practice good personal hygiene to prevent accidental exposure.

Storage

Storage conditions: Store in original container. Keep away from heat and sources of ignition. Storage area should be: cool dry well ventilated out of direct sunlight

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limit(s)

Exposure limits are listed below, if they exist.

Component	Regulation	Type of listing	Value
Electronic grade propylene glycol monomethyl ether acetate	Rohm and Haas	TWA	30 ppm

Materials to avoid	strong bases Strong acids Oxidizing agents
Hazardous decomposition products polymerization	Combustion will generate:, Carbon monoxide, carbon dioxide, oxides of sulfur, nitrogen oxides (NOx), phenols, acrid smoke and irritating fumes, Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicological information on this product or its components appear in this section when such data is available.

Component: **Electronic grade propylene glycol monomethyl ether acetate**

Acute oral toxicity LD50 rat 8,532 mg/kg

Component: **Ethyl lactate**

Acute oral toxicity LD50 rat >2,000 mg/kg

Component: **Electronic grade propylene glycol monomethyl ether acetate**

Acute inhalation toxicity LC50 rat 6 h 23.49 mg/l

Component: **Ethyl lactate**

Acute inhalation toxicity LC50 rat >5,400 mg/m³

Component: **Electronic grade propylene glycol monomethyl ether acetate**

Acute dermal toxicity LD50 rabbit >5,000 mg/kg

Component: **Ethyl lactate**

Acute dermal toxicity LD50 rat >5,000 mg/kg

Component: **Ethyl lactate**

Skin irritation A single application to rabbit skin produced mild irritation.

Component: **Ethyl lactate**

Eye irritation Single application to the rabbit eye produced conjunctival irritation.

Component: **Electronic grade propylene glycol monomethyl ether acetate**

Toxicity to reproduction

Dermal teratology testing of this solvent (with less than 3% beta isomer) revealed no maternally toxic, teratogenic or fetotoxic responses in rats or rabbits exposed to concentrations of 1,000 and 2,000 mg/kg per day.

Component: **Electronic grade propylene glycol monomethyl ether acetate**

Mutagenicity

No significant mutagenic response was observed and the carcinogenic potential of the material is therefore considered to be low.

Component: **Ethyl lactate**

Toxicity to reproduction

No adverse reproductive effects were observed in experimental animals.

12. ECOLOGICAL INFORMATION

Ecotoxicological information on this product or its components appear in this section when such data is available.

Electronic grade propylene glycol monomethyl ether acetate

Ecotoxicity effects

Toxicity to fish	LC50 Fathead minnow (Pimephales promelas) 96 h 161 mg/l
Toxicity to aquatic invertebrates	EC50 Daphnia magna 48 h >500 mg/l

Ethyl lactate

Ecotoxicity effects	
Toxicity to aquatic invertebrates	EC50 Daphnia magna 48 h 683 mg/l

13. DISPOSAL CONSIDERATIONS

Environmental precautions: Prevent the material from entering drains or water courses. Do not discharge directly to a water source. Advise Authorities if spillage has entered watercourse or sewer or has contaminated soil or vegetation.

Disposal

Dispose in accordance with all local, state (provincial), and federal regulations. Incineration is the recommended method of disposal for containers. Under RCRA, it is the responsibility of the product's user to determine at the time of disposal, whether the product meets RCRA criteria for hazardous waste. This is because the product uses, transformations, mixtures, processes, etc. may render the resulting materials hazardous.

Do not remove label until container is thoroughly cleaned. Empty containers may contain hazardous residues. This material and its container must be disposed of in a safe way.

14. TRANSPORT INFORMATION**DOT**

Not regulated per 49CFR 173.150(f)(2)

IMO/IMDG

Proper shipping name	RESIN SOLUTION
UN-No	UN 1866
Class	3
Packing group	III

Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations

15. REGULATORY INFORMATION

SARA TITLE III: Section 311/312 Categorizations (40CFR370): Immediate, delayed, flammability hazard

SARA TITLE III: Section 313 Information (40CFR372)

This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.

US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D):

US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)
This product contains the following substance(s) which are subject to Section 12(b) export notification:
TSCA_12B Components: Acetonitrile 75-05-8

US. Toxic Substances Control Act (TSCA) All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

California (Proposition 65)

This product contains a component or components known to the state of California to cause cancer and/or reproductive harm.

Components: Formaldehyde 50-00-0

16. OTHER INFORMATION

Hazard Rating

	Health	Fire	Reactivity
NFPA	2	2	0

Legend

ACGIH	American Conference of Governmental Industrial Hygienists
BAc	Butyl acetate
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit (STEL):
TLV	Threshold Limit Value
TWA	Time Weighted Average (TWA):
	Bar denotes a revision from prior MSDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Version: 3.2
 Print Date: 02/19/2014
 Layout 000101085808